

**COMPOSITE PIPE APPLICATIONS
AND DESIGN FACTORS TO
EXTEND SYSTEM LIFE**

PRESENTATION AGENDA

- Composite Pipe Design
- Composite Pipe Benefits & Limitations
- Design Factors to Extend Life
- Questions



What Is Composite Pipe?

- Plastic inner liner for corrosion resistance
- Reinforcement layer made of high strength materials examples: fiberglass, aramid fiber, steel
- Might include an epoxy layer
- External Jacket made of similar material to inner liner to protect and contain reinforcement layer
- Referred to as RTP Reinforced Thermoplastic Pipe or SCP Spoolable Composite Pipe
- Can be supplied on reels, in coils or stick lengths




Composite Pipe Industry Standards

- API RP 15S
- ASME B31
- ASME Composite pipe standard in development
- International regulations include local codes
 - CSA Z662 – Canada pipeline construction standard includes composite pipes
 - NTC 3728 – Colombia
 - NOCs have developed internal standards including Saudi Aramco, KOC, YPF Argentina



Composite Pipe Pressure Ratings

- Steel reinforced pipe is rated on wall thickness and short term burst tests
- Fiber reinforced pipe is rated on regression testing per ASTM D2992



PSF = 0.67 as per API 15S
 SFF = 0.67 as per CSA Z662



COMPOSITE PIPE BENEFITS

1 Corrosion Resistance

2 Erosion Resistance

3 Installation Time and Cost

4 Installation Safety



CORROSION RESISTANCE

- Based on historical data corrosion accounts for over 65% of buried pipeline failures in Alberta
- Suitable for corrosive applications
 - H₂S
 - CO₂
 - Produced Water
 - Reinforcement material must be considered
- Liner material resistant to chemical depositions



EROSION RESISTANCE

- Suitable for high solids content
- Plastic materials have increased wear resistance in erosive flow regimes
- Wear of liner material will not impact strength of reinforcement layer


TABLE 1. Wear Rates Of Plastics And Metals Under Abrasive Slurries

| Material | Wear Rates (mm) | | | |
|--------------|-----------------|--------|-----------|--------|
| | Coarse Sand | | Fine Sand | |
| | 7 fps | 15 fps | 7 fps | 15 fps |
| Steel | 0.65 | 1.81 | 0.04 | 0.02 |
| Aluminum | 1.81 | 7.48 | 0.14 | 0.86 |
| Polyethylene | 0.06 | 0.46 | nil | 0.06 |
| ABS | 0.36 | 2.07 | 0.07 | 0.51 |
| Acrylic | 0.99 | 4.10 | 0.17 | 1.42 |



Flexpipe Experience with Corrosive / Erosive Oil & Emulsion Applications

- Number of lines assumes 2300 ft per line



INSTALLATION BENEFITS

- Smaller crew size: 2-4 people versus 10-12 for steel
- Less equipment & Lighter equipment
- Welding and weld inspection costs are eliminated
- Smaller Right Of Way requirement
- Spooled lengths up to and above 3500 ft
- Installation in ½ the time of steel



INSTALLATION BENEFITS

Comparing installation costs of identical 6,500 ft flow lines

| | 6,500 ft FlexPipe Linepipe Flow Line | 6,500 ft Steel Flow Line |
|------------------------|--|---|
| Mobilization: | 2 Trucks: -1 x Track Hoe -1 x Pipe Reels | 6 Loads: -1 x Warehouse -2 x Track Hoe's -1 x Grader -1 x Pipe |
| Equipment: | 1 x 200D series track hoe for stripping top soil, digging, lowering and backfill | 2 x 250 series track hoe's and 1 x grader for top soiling 20 m ROW |
| Manpower: | -1 Supervisor -1 Equipment Operator -2 Laborers | -1 Supervisor -2 Equipment Operators -2 Welders (bead & hot pass/cap) -2 Welder's Helpers -3 Laborers |
| Testing: | -1 digital deadweight -2 recorders | -1 digital deadweight -2 recorders |
| X-Ray: | Not Needed | Required, 100% |
| Risers: | Cathodic protection as required | Coating costs for risers |
| Demobilization: | 2 Trucks: -1x Track Hoe -1x Pipe Reels | 4 Loads: -2x Track Hoe's -1x Grader -1x Misc. equipment and materials |

Composite Pipe Limitations

- Does not fit all applications
 - Pipe diameters
 - Operating pressures
 - Operating temperatures
- Relatively new to industry
 - Composite Pipe has been in use for 15 years versus steel pipe in use for 150+ years
 - Industry knowledge and understanding of Steel Pipe is very well developed
 - Education is needed on composite pipe and composite failure modes
- Not all composite pipe products perform the same
- Regulatory acceptance is not yet universal



Design and Construction Factors to Optimize Composite Pipe Life

Fitting and Riser System


- How repeatable is the fitting installation process? What opportunities are there for human error?
- When over-pressured, does the pipe or fitting fail first?
- As ground settles, how are shear loads next to fittings accounted for?
- What is the available temperature installation window?
- How is wall thickness variation accounted for to ensure distribution fitting clamping force around pipe?



Design and Construction Factors to Optimize Composite Pipe Life

Operating Factors

- Will the pipe grow axially or radially when pressurized? What must be done to compensate for the resulting movement?
- How are permeated gases accounted for?
 - Will service fluids lead to corrosion in composites reinforced with steel?
 - How are annulus spaces vented?
 - For fully bonded composites, how are voids where pressure can build prevented?
- Will pipe for surface lines survive ground fires?
- Will the pipe be used in an area that floods and is additional anchoring needed?
- Will the pipe survive cyclic fatigue due to water hammer?
- Does the supplier offer an application review to identify failure modes and ensure fit?



Design and Construction Factors to Optimize Composite Pipe Life

Installation Quality Control

- How much handling and impact damage can the product resist? Is sand bedding required?
- What is the available pipe installation temperature window?
- Can a third party be trained or does the vendor require that they install the fittings?
- Is detailed documentation of technical, installation, and training procedures provided?
- Is a process for tracking and documenting proper installation procedures provided? Recommend including a QC package in scope of work for third party contractors.



Revision Date: 09-Apr-2023 No. 24-090, Revision No. 04, Origination: Northern CO Dist
 Incorporated 7 Pages

FLEXPIPE SYSTEMS

DAILY FIELD REPORT

Date: _____
 FP ID #: _____

Customer: _____
 Customer Representative: _____

Sub Location: _____
 Construction Contractor: _____

Location GPS/LMS: _____
 Contractor Supervisor: _____

Site/Weather: _____
 Contractor Supervisor: _____

Fittings Installed: _____
 Sketch Provided (Y/N): _____

Fittings Installed: _____
 Tracer wire used: Y N

Photos Taken (Y/N): _____
 All Connections checked for moisture: Y N

Application (Flow Line, Transfer, SWD, etc.): _____
 All Fittings Dimple tagged and black taped: Y N

| Fitting Description | Serial | GPS | SY | Surface Lines Properly Packed and sealed: | Correct Crimp Measurements: |
|---------------------|--------|-----|----|---|---|
| | | | | <input type="checkbox"/> Y <input type="checkbox"/> N | <input type="checkbox"/> Y <input type="checkbox"/> N |
| | | | | Pipe measured to prevent over insertion: | Correct Crimp Measurements: |
| | | | | <input type="checkbox"/> Y <input type="checkbox"/> N | <input type="checkbox"/> Y <input type="checkbox"/> N |
| | | | | End of Pipe Dimple guarded: | Correct Crimp Measurements: |
| | | | | <input type="checkbox"/> Y <input type="checkbox"/> N | <input type="checkbox"/> Y <input type="checkbox"/> N |
| | | | | Clamp was a minimum of 4" from end of sleeve: | Correct Crimp Measurements: |
| | | | | <input type="checkbox"/> Y <input type="checkbox"/> N | <input type="checkbox"/> Y <input type="checkbox"/> N |
| | | | | Surface Lines Properly Packed and sealed: | Correct Crimp Measurements: |
| | | | | <input type="checkbox"/> Y <input type="checkbox"/> N | <input type="checkbox"/> Y <input type="checkbox"/> N |
| | | | | Fittings inspected for damage: | Correct Crimp Measurements: |
| | | | | <input type="checkbox"/> Y <input type="checkbox"/> N | <input type="checkbox"/> Y <input type="checkbox"/> N |
| | | | | Weld hole in place and free from distortion: | Correct Crimp Measurements: |
| | | | | <input type="checkbox"/> Y <input type="checkbox"/> N | <input type="checkbox"/> Y <input type="checkbox"/> N |
| | | | | Any holes have been repaired correctly: | Correct Crimp Measurements: |
| | | | | <input type="checkbox"/> Y <input type="checkbox"/> N | <input type="checkbox"/> Y <input type="checkbox"/> N |
| | | | | Equipment operates correctly @ 1/4 PSI: | Correct Crimp Measurements: |
| | | | | <input type="checkbox"/> Y <input type="checkbox"/> N | <input type="checkbox"/> Y <input type="checkbox"/> N |
| | | | | Correct size fittings with size of pipe: | Correct Crimp Measurements: |
| | | | | <input type="checkbox"/> Y <input type="checkbox"/> N | <input type="checkbox"/> Y <input type="checkbox"/> N |
| | | | | Any loose ends and partial ends properly sealed capped: | Correct Crimp Measurements: |
| | | | | <input type="checkbox"/> Y <input type="checkbox"/> N | <input type="checkbox"/> Y <input type="checkbox"/> N |

Pipe Run #'s: _____ Pipe Size: _____ Length: _____
 Pipe and Fitting installation is in accordance with training provided by Flexpipe Systems and the check list above.

Name of Installation Tech: _____ Signature: _____ Date: _____
 Name of Installation Tech: _____ Signature: _____ Date: _____

I hereby acknowledge that the installation provided follows all procedures and is in place in Flexpipe systems in accordance to the training provided by Flexpipe Systems & installation guide 1.0 10/18/23/21

Lead Installation Rep: _____ Customer Rep: _____



Composite pipe addresses corrosion and erosion issues while saving installation time and cost



Verify application fit and use installation quality control systems to maximize value and extend system life



FLEXPIPE OFFERS THE COMPLETE SOLUTION

Provide end-to-end solution for your individual needs

